

**AAR Manual of Standards and Recommended Practices
Car Construction Fundamentals and Details**

ALPHABETICAL TABLE OF CONTENTS

Subject	Standard	Page
Accelerated Fatigue Test Specification for Increased Life Status Applications	S-2046	C[S-2046]373
Anti-Pilferage Device—Boxcar Plug Door	S-2050	C[S-2050]385
Anti-Pilferage Device—Boxcar Sliding Door	S-2049	C[S-2049]383
Batten Bars	S-2039	C[S-2039]201
Body Center Plate Gauge—14-in. and 16-in. Diameter	S-211	C[S-211]29
Body Center Plate Relief	S-258	C[S-258]139
Body Center Plate, Cast Steel or Forged—for Freight Cars with 14-in. Center Plates	S-206	C[S-206]25
Body Center Plate, Cast Steel or Forged—for Freight Cars with 16-in. Center Plates	S-207	C[S-207]27
Body Center Plate, Low Profile	S-2055	C[S-2055]395
Body Center Plate, Separable—Surface Finish	S-204	C[S-204]21
Brake Control Valves—Mount-Configuration Designs as Related to Field Vibration	RP-401	C[RP-401]423
Car Builder Certification	S-2034	C[S-2034]169
Card Holder—Bad Order	S-2008	C[S-2008]151
Center Bowl Liner and Lubricant—Double-Stack Container Car	RP-261	C[RP-261]419
Center Pin—Freight Car	S-265	C[S-265]143
Center Sill Section—Welding Notes	S-267	C[S-267]147
Center Sill Section, Rolled Steel	S-266	C[S-266]145
Clearance Diagram—Interface Between a Well Car and a Container Equipped with a Refrigerator/Heater Unit	S-2054	C[S-2054]393
Combined Striker and Front Draft Lug Tolerances	S-255	C[S-255]137
Container Interface—Well Car, 53 ft	S-2053	C[S-2053]391
Coupler, Height Adjustment	S-203	C[S-203]19
Decking, Wood—for Open Top Cars	RP-206	C[RP-206]399
Door Air Lines—Location of End Cocks	S-252	C[S-252]127
Door Puller Bracket, Application to Intermediate Post	S-249	C[S-249]125
DOT Placard Location	S-229	C[S-229]95
Draft Arrangement, E60 Coupler, 24 5/8 in. Pocket—Striker Applied by Welding	S-239	C[S-239]115
Draft Arrangement, E68 Coupler, 24 5/8-in. Pocket	S-243	C[S-243]117
Draft Arrangement, E69 Coupler, 24 5/8-in. Pocket	S-244	C[S-244]119
Draft Arrangement, F70 Coupler, 24 5/8-in. Pocket—Striker Applied by Welding	S-245	C[S-245]121
Draft Arrangement, F79 Coupler, 24 5/8-in. Pocket	S-247	C[S-247]123
Draft Pocket Tolerances	S-254	C[S-254]135
Electronic Distribution Format For Engineering Drawings	RP-940	C[RP-940]441
Floor, Flat Steel—Freight Cars 50,000-, 60,000-, 70,000- or 80,000-lb Capacities	M-908	C[M-908]7

IMPLEMENTED 08/12/2014

**AAR Manual of Standards and Recommended Practices
Car Construction Fundamentals and Details**

Subject	Standard	Page
Floor, Nailable Steel—Freight Cars	M-964	C[M-964]13
Free/Unrestricted Interchange for 286,000 lb Gross Rail Load Cars	S-286	C[S-286]149
Gravity Outlet Gates, New—for Covered Hopper Cars	S-233	C[S-233]99
Handholds, Safety Railings, and Ladder Treads	S-224	C[S-224]79
Hold-Down Clips—Gondolas, Side Sheet Mounted	RP-233	C[RP-233]413
Hold-Down Clips—Gondolas, Top Cord Mounted	RP-234	C[RP-234]415
Hopper Car—End for Door Operating Shaft	S-2025	C[S-2025]153
Hopper Car—Grain Service	RP-258	C[RP-258]417
Hopper Car, Covered—for Transport of Oxidizing Commodities	M-800	C[M-800]1
Hopper Car, Covered—Pressurized During Unloading and In-transit	M-801	C[M-801]3
Hopper Car, Open Top, in Shaker Service—Design Features	RP-200	C[RP-200]397
Identification Plate—Boxcar Doors	S-217	C[S-217]63
Ladder, End and Side—Configuration	RP-232	C[RP-232]411
Lading Strap Anchor Arrangement and Use—for Flatcars	S-230	C[S-230]97
Lifting Freight Cars	S-234	C[S-234]107
Performance Requirements for Refrigerated Boxcar Fuel Tanks	RP-905	C[RP-905]439
Performance Specification for Trains Used to Carry High-Level Radioactive Material	S-2043	C[S-2043]211
Plate B-1—Maximum Width of Cars with Various Truck Centers	S-2027	C[S-2027]157
Plate B—Equipment Diagram for Unrestricted Interchange Service	S-2026	C[S-2026]155
Plate C-1—Maximum Width of Cars with Various Truck Centers	S-2029	C[S-2029]161
Plate C—Equipment Diagram for Limited Interchange Service	S-2028	C[S-2028]159
Plate D—Obtaining Maximum Allowable Width of Car, Other Than at Centerline of Car, for Unrestricted (Plate B-1) and Limited (Plates C-1, H-1, J-1, and K-1) Interchange Service	S-2030	C[S-2030]163
Plate E—Equipment Diagram for Limited Interchange Service	S-2031	C[S-2031]165
Plate F—Equipment Diagram for Limited Interchange Service	S-2032	C[S-2032]167
Plate H-1—Maximum Width of Cars with Various Truck Centers	S-2041	C[S-2041]207
Plate H—Equipment Diagram for Limited Interchange Service	S-2040	C[S-2040]205
Plate J—Equipment Diagram for Limited Interchange Service	S-2047	C[S-2047]379
Plate J1—Maximum Width of Cars with Various Truck Centers	S-2051	C[S-2051]387
Plate K—Clearance Diagram for Limited Interchange Service	S-2048	C[S-2048]381
Plate K1—Maximum Width of Cars with Various Truck Centers	S-2052	C[S-2052]389
Rack Car, Multilevel, with or without Door or Roof, Enclosed—Safety Appliance Standards	S-2038	C[S-2038]197
Rail Car, 286,000-lb Gross Weight	S-259	C[S-259]141
Remote Monitoring Equipment, Installation	S-2045	C[S-2045]367
Running Boards, Walkways, Brake Steps, and End Platforms	S-226	C[S-226]83
Safety Appliance Requirements for Freight Cars	S-2044	C[S-2044]257
Safety Appliances for Bulkhead Flatcars, Including Pulpwood Cars	S-219	C[S-219]65
Safety Appliances for Special Service High-Side Gondolas with Fixed Ends	S-220	C[S-220]73

IMPLEMENTED 08/12/2014

**AAR Manual of Standards and Recommended Practices
Car Construction Fundamentals and Details**

Subject	Standard	Page
Safety Hangers and Retainers—for Freight Car Doors	S-215	C[S-215]61
Side Bearing Wear Plate—Car Body	S-235	C[S-235]109
Side Door, Boxcar—Plug Type	S-213	C[S-213]45
Side Door, Boxcar—Sliding Type	S-212	C[S-212]31
Side Handhold, Additional—Hopper and High-Side Gondola Cars	S-2035	C[S-2035]185
Sill Step Performance	S-2042	C[S-2042]207
Spark Shield—Wooden Deck Cars with Cast Iron Brake Shoes	S-225	C[S-225]81
Stake Pocket—for Flatcars	RP-209	C[RP-209]403
Stake Pocket—Permanent	RP-208	C[RP-208]401
Striker Casting, Cast Steel	RP-2017	C[RP-2017]443
Striker, Cast Steel, F70 Coupler Design, 24 5/8-in. Draft Gear Pocket—Parts and Assembly	S-238	C[S-238]113
Striker, Cast Steel, F70 Coupler Design, 24 5/8-in. Draft Gear Pocket—Welded Application	S-236	C[S-236]111
Temperature—for Car Structures and Components	S-2036	C[S-2036]187
Train Coal Car, 100-Ton Nominal Capacity, with Train Positioner—Clearance Diagram	S-253	C[S-253]133
Trough Hatch Cover	S-2037	C[S-2037]189
Universal Pocket—Typical Sections and Notes	RP-231	C[RP-231]409
Universal Pocket, 10-in. Cushion, Low Deck—E69 Coupler	RP-228	C[RP-228]407
Universal Pocket, 15-in. Cushion, E69 Coupler	RP-227	C[RP-227]405
Walkways, Alternate—At Sides of Double-Stack Car Wells	S-227	C[S-227]91

IMPLEMENTED 08/12/2014

**AAR Manual of Standards and Recommended Practices
Car Construction Fundamentals and Details**

NUMERICAL TABLE OF CONTENTS

Standard	Subject	Page
M-800	Hopper Car, Covered—for Transport of Oxidizing Commodities	C[M-800]1
M-801	Hopper Car, Covered—Pressurized During Unloading and In-transit	C[M-801]3
M-908	Floor, Flat Steel—Freight Cars 50,000-, 60,000-, 70,000- or 80,000-lb Capacities	C[M-908]7
M-964	Floor, Nailable Steel—Freight Cars	C[M-964]13
RP-200	Hopper Car, Open Top, in Shaker Service—Design Features	C[RP-200]397
RP-206	Decking, Wood—for Open Top Cars	C[RP-206]399
RP-208	Stake Pocket—Permanent	C[RP-208]401
RP-209	Stake Pocket—for Flatcars	C[RP-209]403
RP-227	Universal Pocket, 15-in. Cushion, E69 Coupler	C[RP-227]405
RP-228	Universal Pocket, 10-in. Cushion, Low Deck—E69 Coupler	C[RP-228]407
RP-231	Universal Pocket—Typical Sections and Notes	C[RP-231]409
RP-232	Ladder, End and Side—Configuration	C[RP-232]411
RP-233	Hold-Down Clips—Gondolas, Side Sheet Mounted	C[RP-233]413
RP-234	Hold-Down Clips—Gondolas, Top Cord Mounted	C[RP-234]415
RP-258	Hopper Car—Grain Service	C[RP-258]417
RP-261	Center Bowl Liner and Lubricant—Double-Stack Container Car	C[RP-261]419
RP-401	Brake Control Valves—Mount-Configuration Designs as Related to Field Vibration	C[RP-401]423
RP-905	Performance Requirements for Refrigerated Boxcar Fuel Tanks	C[RP-905]439
RP-940	Electronic Distribution Format For Engineering Drawings	C[RP-940]441
RP-2017	Striker Casting, Cast Steel	C[RP-2017]443
S-203	Coupler, Height Adjustment	C[S-203]19
S-204	Body Center Plate, Separable—Surface Finish	C[S-204]21
S-206	Body Center Plate, Cast Steel or Forged—for Freight Cars with 14-in. Center Plates	C[S-206]25
S-207	Body Center Plate, Cast Steel or Forged—for Freight Cars with 16-in. Center Plates	C[S-207]27
S-211	Body Center Plate Gauge—14-in. and 16-in. Diameter	C[S-211]29
S-212	Side Door, Boxcar—Sliding Type	C[S-212]31
S-213	Side Door, Boxcar—Plug Type	C[S-213]45
S-215	Safety Hangers and Retainers—for Freight Car Doors	C[S-215]61
S-217	Identification Plate—Boxcar Doors	C[S-217]63
S-219	Safety Appliances for Bulkhead Flatcars, Including Pulpwood Cars	C[S-219]65
S-220	Safety Appliances for Special Service High-Side Gondolas with Fixed Ends	C[S-220]73
S-224	Handholds, Safety Railings, and Ladder Treads	C[S-224]79
S-225	Spark Shield—Wooden Deck Cars with Cast Iron Brake Shoes	C[S-225]81
S-226	Running Boards, Walkways, Brake Steps, and End Platforms	C[S-226]83
S-227	Walkways, Alternate—At Sides of Double-Stack Car Wells	C[S-227]91

IMPLEMENTED 08/12/2014

**AAR Manual of Standards and Recommended Practices
Car Construction Fundamentals and Details**

Standard	Subject	Page
S-229	DOT Placard Location	C[S-229]95
S-230	Lading Strap Anchor Arrangement and Use—for Flatcars	C[S-230]97
S-233	Gravity Outlet Gates, New—for Covered Hopper Cars	C[S-233]99
S-234	Lifting Freight Cars	C[S-234]107
S-235	Side Bearing Wear Plate—Car Body	C[S-235]109
S-236	Striker, Cast Steel, F70 Coupler Design, 24 5/8-in. Draft Gear Pocket—Welded Application	C[S-236]111
S-238	Striker, Cast Steel, F70 Coupler Design, 24 5/8-in. Draft Gear Pocket—Parts and Assembly	C[S-238]113
S-239	Draft Arrangement, E60 Coupler, 24 5/8 in. Pocket—Striker Applied by Welding	C[S-239]115
S-243	Draft Arrangement, E68 Coupler, 24 5/8-in. Pocket	C[S-243]117
S-244	Draft Arrangement, E69 Coupler, 24 5/8-in. Pocket	C[S-244]119
S-245	Draft Arrangement, F70 Coupler, 24 5/8-in. Pocket—Striker Applied by Welding	C[S-245]121
S-247	Draft Arrangement, F79 Coupler, 24 5/8-in. Pocket	C[S-247]123
S-249	Door Puller Bracket, Application to Intermediate Post	C[S-249]125
S-252	Door Air Lines—Location of End Cocks	C[S-252]127
S-253	Train Coal Car, 100-Ton Nominal Capacity, with Train Positioner—Clearance Diagram	C[S-253]133
S-254	Draft Pocket Tolerances	C[S-254]135
S-255	Combined Striker and Front Draft Lug Tolerances	C[S-255]137
S-258	Body Center Plate Relief	C[S-258]139
S-259	Rail Car, 286,000-lb Gross Weight	C[S-259]141
S-265	Center Pin—Freight Car	C[S-265]143
S-266	Center Sill Section, Rolled Steel	C[S-266]145
S-267	Center Sill Section—Welding Notes	C[S-267]147
S-286	Free/Unrestricted Interchange for 286,000 lb Gross Rail Load Cars	C[S-286]149
S-2008	Card Holder—Bad Order	C[S-2008]151
S-2025	Hopper Car—End for Door Operating Shaft	C[S-2025]153
S-2026	Plate B—Equipment Diagram for Unrestricted Interchange Service	C[S-2026]155
S-2027	Plate B-1—Maximum Width of Cars with Various Truck Centers	C[S-2027]157
S-2028	Plate C—Equipment Diagram for Limited Interchange Service	C[S-2028]159
S-2029	Plate C-1—Maximum Width of Cars with Various Truck Centers	C[S-2029]161
S-2030	Plate D—Obtaining Maximum Allowable Width of Car, Other Than at Centerline of Car, for Unrestricted (Plate B-1) and Limited (Plates C-1, H-1, J-1, and K-1) Interchange Service	C[S-2030]163
S-2031	Plate E—Equipment Diagram for Limited Interchange Service	C[S-2031]165
S-2032	Plate F—Equipment Diagram for Limited Interchange Service	C[S-2032]167
S-2034	Car Builder Certification	C[S-2034]169
S-2035	Side Handhold, Additional—Hopper and High-Side Gondola Cars	C[S-2035]185
S-2036	Temperature—for Car Structures and Components	C[S-2036]187
S-2037	Trough Hatch Cover	C[S-2037]189

IMPLEMENTED 08/12/2014

**AAR Manual of Standards and Recommended Practices
Car Construction Fundamentals and Details**

Standard	Subject	Page
S-2038	Rack Car, Multilevel, with or without Door or Roof, Enclosed—Safety Appliance Standards	C[S-2038]197
S-2039	Batten Bars	C[S-2039]201
S-2040	Plate H—Equipment Diagram for Limited Interchange Service	C[S-2040]205
S-2041	Plate H-1—Maximum Width of Cars with Various Truck Centers	C[S-2041]207
S-2042	Sill Step Performance	C[S-2041]207
S-2043	Performance Specification for Trains Used to Carry High-Level Radioactive Material	C[S-2043]211
S-2044	Safety Appliance Requirements for Freight Cars	C[S-2044]257
S-2045	Remote Monitoring Equipment, Installation	C[S-2045]367
S-2046	Accelerated Fatigue Test Specification for Increased Life Status Applications	C[S-2046]373
S-2047	Plate J—Equipment Diagram for Limited Interchange Service	C[S-2047]379
S-2048	Plate K—Clearance Diagram for Limited Interchange Service	C[S-2048]381
S-2049	Anti-Pilferage Device—Boxcar Sliding Door	C[S-2049]383
S-2050	Anti-Pilferage Device—Boxcar Plug Door	C[S-2050]385
S-2051	Plate J1—Maximum Width of Cars with Various Truck Centers	C[S-2051]387
S-2052	Plate K1—Maximum Width of Cars with Various Truck Centers	C[S-2052]389
S-2053	Container Interface—Well Car, 53 ft	C[S-2053]391
S-2054	Clearance Diagram—Interface Between a Well Car and a Container Equipped with a Refrigerator/Heater Unit	C[S-2054]393
S-2055	Body Center Plate, Low Profile	C[S-2055]395

IMPLEMENTED 08/12/2014